



Suprabha's tryst with anti-corrosion dates back to the '70s with its ground breaking innovation of eco-friendly Suprabha Vapour Corrosion Inhibitor (SVCI*).

VCI's heralded a new era in the world of anti corrosion solutions and Suprabha became India's first eco-friendly SVCI Provider. Better known today as a Corrosion Solutions Provider, Suprabha is an INR 10 billion group with an ISO: TS 16949 Certification. Suprabha has numerous innovations and awards to its credit.

Rustopliq

Water based rust preventive liquids

protection period is however sufficiently long to ensure in-plant and in-process protection. These products are ideal for protection from few hours to few days. Repetition of application however can extend the period of protection as desired.

This simple method of surface protection obviates the need for costly rust preventive oils and installation of conventional multi-tank system to clean the surface off oil, rust etc. on components by following cumbersome process. It completely eliminates the pollution caused by the cleaning system.

As there is no loss of liquid due to evaporation, usage of SVCI Water based eco-friendly liquid for rust prevention will be economical.

- Protected areas of the component do not require cleaning / degreasing thereby saves time and effort
- Components when additionally wrapped in Suprabha Rustopaper can offer long periods of dry protection

Special Features

- 100% eco-friendly and environmentally safe
- Neutralisation action removes acidic traces present in the surroundings and avoids any further attack on the metals.
- Protection against rust during manufacturing process
- Eliminates the ill-effect of the reminiscence of coolant and fingerprints
- Soluble in coolant hence eliminates the need for removing protective coating
- Non-toxic, non-hazardous, non-inflammable formulation and mild fragrance makes it ideal for in-plant use
- No need for wrapping and oiling during storage



An Eskimo's home is built of ice yet it keeps him warm. Similarly, water although known to promote corrosion in metals, especially iron and steel, can be an excellent solvent base for some of the environmentally safe chemicals such as prophylactic agents to control corrosion for short periods. The



PRODUCT CODE	DESCRIPTION	APPLICATIONS	SPECIAL FEATURES	PROTECTION PERIOD
SVCI 301	SVCI liquid applied by brush, dip or spray	Short term rust prevention for Ferrous items	--	25-30 days
SVCI 302	SVCI liquid applied by brush, dip or spray	Short term rust prevention for Ferrous items	<ul style="list-style-type: none"> Neutralisation of acid traces Leaves a powdery coating when dry 	25-30 days
SVCI 302K SVCI 302M SVCI 302V	Non-film forming SVCI liquid applied by brush, dip or spray	Rust prevention for Ferrous items	<ul style="list-style-type: none"> Neutralisation of acid traces No film 	25-30 days
SVCI 304	Film forming SVCI liquid	Rust prevention for Ferrous items	<ul style="list-style-type: none"> Components can be directly welded / painted / taken for assembly Biodegradable 	3-4 months
SVCI 305	Non-film forming SVCI liquid	Rust prevention for Ferrous items	<ul style="list-style-type: none"> No film Components can be directly welded / painted / taken for assembly Biodegradable 	3-4 months
SVCI 312-S	Water based SVCI liquid	Protection for silver & silver plated components	<ul style="list-style-type: none"> Ready to use No film 	1-2 months
SVCI 321	SVCI Nitrite - free additive to quenching medium	Corrosion inhibition additive for spot welding or quenching process Use - 1:40 ratio	Completely biodegradable	7-10 days
SVCI 325	Corrosion Inhibitor to aqueous solution	Good emulsion stabiliser	--	10-15 days
SVCI 331	SVCI additive for soluble oil coolants	Rust inhibition during machining operations	Use - 1:40/1:25 ratio in coolant bath	7-10 days
SVCI 332	SVCI Nitrite, Phosphate free additive for soluble oil coolants	Rust inhibition during machining operations	Use - 1:40/1:25 ratio in coolant bath	7-10 days
SVCI 340	SVCI liquid applied by brush, dip or spray	Protection to bimetal & multi metal combination	<ul style="list-style-type: none"> Most suitable for Copper & Brass No film 	Short term
SVCI 355	Polythene emulsion / film forming SVCI liquid	Protection of Ferrous items	Ready to use	8-10 months
BAC 333	Bactrol - To prevent corrosion due to bacteria	For controlling bacteria growth in coolant/aqueous baths	To be used at 0.01% of bath	Extends the life of coolant by at least 1.5 times

* SVCI is the registered trade mark of Suprabha

MSDS available on request.

Suprabha Protective Products Pvt. Ltd.

Bhandari Apts., First Floor, 373 Somwar Peth,
Pune – 411 001, India.
Tel. : +91 20 2606 1123, +91 20 2606 1238
Fax : +91 20 2606 1103
e-mail : sales@suprabha.com
www.suprabha.com

Bengaluru • Chennai • Coimbatore • Delhi • Hyderabad • Indore • Jamshedpur • Kolkata • Ludhiana • Mumbai • Pune • Uttaranchal • Vadodara



All statements, technical information and recommendation contained herein are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed. Seller warrants product will be free from defects when shipped to user. Seller's only obligation shall be to replace within sixty days after the date of purchase, such quantity of product found defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the products. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. The warranty offered in connection with the product is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose.